

max. 350 bar

KR munstycken

KR munstycken tillverkas av härdat eller rostfritt stål. Alla munstycken har strålvinkel 30 grader bakåt och möjlighet till front-strålning.



Kapitel
chapter



2.8

Sewer and Pipe Cleaning Nozzles

Long-life Sewer and Pipe Cleaning Nozzles with wrench flats at the connection. They are suitable for removing mud deposits and obstructions. VS= Forward jet RS= Backward jet. The angle for the backward jet are for all nozzles 30°. Ceramic inserts you will find on chapter IV. Adapters for reducing or increasing connection and Rotating Joints you will find at chapter VI.

/ Hardened Steel

Order-No.	Designation	Weight Kg	Dimension mm L x Ø	Connection	Drills Keramik / ceramik	Scope of application from
T101	KR 08	0,15	40x30	1/2"	VS 1x M6 RS 6 x drilled	Ab / ₂ DN 60
T102	KR 08	0,15	40x30	1/2"	VS 1x M6 RS 8 x drilled	Ab / ₂ DN 60
T103	KR 09	0,20	50x30	1/2"	VS 1x M6 RS 6 x drilled	Ab / ₂ DN 70
T104	KR 09	0,20	50x30	1/2"	VS 1x M6 RS 8 x drilled	Ab / ₂ DN 70
T105	KR 10	0,30	50x40	3/4"	VS 1x M6 RS 8 x drilled	Ab / ₂ DN 100
T106	KR 11	0,35	65x40	3/4"	VS 1x M6 RS 8 x drilled	Ab / ₂ DN 100
T107	KR 12	0,40	60x50	1"	VS 1x M6 RS 10 x drilled	Ab / ₂ DN 150
T108	KR 13	0,50	80x50	1"	VS 1x M6 RS 10 x drilled	Ab / ₂ DN 150
T109	KR 14	0,95	100x60	1 1/4"	VS 1x M6 RS 10 x drilled	Ab / ₂ DN 200
T110	KR 15	1,00	115x70	1 1/2"	VS 1x M6 RS 12 x drilled	Ab / ₂ DN 200

/ Stainless Steel

T151	KR 01VA	0,08	18x16	1/8"	VS 1x drilled RS 3 x drilled	Ab / ₂ DN 30
T152	KR 02VA	0,08	18x18	1/4"	VS 1x drilled RS 3 x drilled	Ab / ₂ DN 30
T153	KR 03VA	0,08	18x18	1/4"	VS 1x drilled RS 6 x drilled	Ab / ₂ DN 30
T154	KR 04VA	0,09	30x17	1/4"	VS 1x drilled RS 3 x drilled	Ab / ₂ DN 50
T155	KR 05VA	0,09	30x17	1/4"	VS 1x drilled RS 6 x drilled	Ab / ₂ DN 50
T156	KR 07VA	0,10	35x25	3/8"	VS 1x drilled RS 6 x drilled	Ab / ₂ DN 50
T157	KR 08VA	0,15	40x30	1/2"	VS 1x drilled RS 6 x drilled	Ab / ₂ DN 60
T158	KR 08VA	0,15	40x30	1/2"	VS 1x drilled RS 8 x drilled	Ab / ₂ DN 60
T159	KR 09VA	0,20	50x30	1/2"	VS 1x drilled RS 6 x drilled	Ab / ₂ DN 70
T160	KR 09VA	0,20	50x30	1/2"	VS 1x drilled RS 8 x drilled	Ab / ₂ DN 70
T161	KR 10VA	0,30	50x40	3/4"	VS 1x drilled RS 8 x drilled	Ab / ₂ DN 100
T162	KR 11VA	0,35	65x40	3/4"	VS 1x drilled RS 8 x drilled	Ab / ₂ DN 100

Hemsida: www.vretmaskin.se, E-post: info@vretmaskin.se

