

max. 350 bar

Aquadrill

Dessa munstycken wobblar i ledningen, lämpliga för helt förstoppade ledningar och fettbelagda ledningar från dia 60 till 250 mm.



Order-No.	Designation	Weight kg	Dimension mm Lg	Connection	Inserts	Scope of application from
0624	AD 12	0,35	65 Ø34	1/2"	R56 x M4	DN 60 - 300
0625	AD 1	0,90	95 Ø50	1"	R58 x M6	DN 60 - 300

Aquadrill

Frontstream rotation nozzle with ceramic insert for DN 60 - DN 250, 150 bar waterpressure and up to 60° C water temperatures, special for complete blocked pipes to remove grease in fallpipes.

The spinning driller frontjet of this nozzle produces a multiple of the standard impact energy than the frontjet of a rodding nozzle. This nozzle needs only 25 % of the total watersupply there is more water for traction / cleaning and removal.

Tipp:
To use with rotating joints!

Hurricane

Detta högeffektiva roterande munstycke med hög dragkraft. Bakåtstrålning 15 grader.



Hurricane

High performance rotation nozzle provides a very good cleaning and the strategically based rearjets result in high pulling power. For circular cleaning and before camera inspection.

Order-No.	Designation	Weight kg	Dimension mm Lg	Connection	Inserts	Scope of application from
9996	RTHU 1	3,14	175 Ø70	1"	1xV5 M6 ceramik 6 Ros M6 ceramik 6 RS M6 ceramik	DN 60 - 300
9997	RTHU 14	3,14	175 Ø70	1 1/4"	1xV5 M6 ceramik 6 Ros M6 ceramik 6 RS M6 ceramik	DN 60 - 300

Hemsida: www.vretmaskin.se. E-post: info@vretmaskin.se

Kapitel
chapter



2.12

