

max. 350 bar

Explosive  
chapter

1.1

## Bulldozer

Muskelmunstycket för avlopp med minsta diameter 200 mm. Konstruerat för att alltid ligga rättvänd i röret, används alltid med svivel mellan munstycke och slang.



Order-No.	Designation	Weight Kg	Dimension mm	Connection	Inserts	Scope of application from
0201	B 00	4,5	Lx B x H 180x110x100	1/2"	6 x M 10x1 ceramic	Ab 1/2 DN 200
0202	B 01	7,0	Lx B x H 320x160x150	3/4"	6 x M 10x1 ceramic	Ab 1/2 DN 200
0203	B 02	13,0	Lx B x H 350x160x150	1"	6 x M 10x1 ceramic	Ab 1/2 DN 400
0204	B 03	22,0	Lx B x H 450x190x180	1"	8 x M 10x1 ceramic	Ab 1/2 DN 500
0205	B 04	37,0	Lx B x H 600x240x210	1 1/4"	10 x M 10x1 ceramic	Ab 1/2 DN 600
0206	B 05	37,0	Lx B x H 600x240x210	1 1/2"	10 x M 10x1 ceramic	Ab 1/2 DN 800

## Bulldozer

The muscle men for sewers with a nominal width of DN 200 mm sets new standards. The Bulldozer system concentrates the whole power on the sewer invert, thus achieving optimum efficiency.

The advantages are:

- cleaning times reduced considerably
- water consumption reduced
- more thorough cleaning
- deep cleaning in sewers with high water flow (no floating)
- easy sliding forward and backward due to edge runners
- removable runners made of hardened Steel

All Bulldozers will be delivered with rotating joints except Bulldozer B 00. The angles of the nozzles are 0°- 45° backwards and 4° to the bottom. Ceramic inserts you will find on chapter IV. Adapters for reducing or increasing connection and Rotating Joints you will find at chapter VI.

Hemsida: [www.vretmaskin.se](http://www.vretmaskin.se), E-post: [info@vretmaskin.se](mailto:info@vretmaskin.se)