


max. 350 bar

Hålborrade munstycken

Dessa munstycken är urborrade i mitten för att minska vikten och kunna dra slangen långt. Smala strålvinklar 15 - 20 grader.



Hollow Nozzle

This nozzle from hardened steel is famous for very strong pull and cleaning results. Very light construction and small angles.

To use to remove sedimentation, stones and sand.

Order-No.	Designation	Weight kg	Dimension mm L x Ø	Connection	Inserts	Scope of application from
4501	H 75	2,6	143 x 75	1"	2 x 4M 10x1 ceramic	Ab / ₂ DN 250
4502	H 95	5,8	205 x 95	1"	2 x 4M 10x1 ceramic	Ab / ₂ DN 400
4502-14	H 114	5,8	205 x 95	1 1/4"	2 x 8M 10x1 ceramic	Ab / ₂ DN 400

Deponimunstycken

Dessa munstycken kan dra lätta slangar upp till 400 meter! Munstycke B275 är tillverkat i ett material som inte ger gnistor, skall användas då man är osäker om det är explosionsfara eller ej.



Order-No.	Designation	Weight KG	Dimension mm LxØ	Connection	Inserts	Scope of application from
0401	B 180	3,5	140 x 80	1"	8 x M10x1 Keramik / ceramic	Ab / ₂ DN 200
0402	B 200	8,0	190 x 100	1"	10x M 10x1 Keramik / ceramic	Ab / ₂ DN 250
0403	B 250	13,0	230 x 110	1 1/4"	10x M 10x1 Keramik / ceramic	Ab / ₂ DN 400
0404	B 275	3,3	180 x 85	1"	7x M 10x1 Keramik / ceramic	Ab / ₂ DN 250

Dump Nozzles

Special cleaning nozzle for drainage pipes with a very high pressure force and cleaning performance. Connected with a light weight hose and an appropriate water performance, this special nozzle can cover up to 400 metres. Made of hardened steel. The dump nozzle B 275 is especially suitable in hazardous areas (e.g. in barracks with unknown remains) They are made of a special material and will be free of sparks and very light.

The angle of the nozzles will be 5°/8° and regarding the dump nozzle B 275 respectively only 5°.

Ceramic inserts you will find on chapter IV. Adapters for reducing or increasing connection and Rotating Joints you will find at chapter VI.

Hemsida: www.vretmaskin.se, E-post: info@vretmaskin.se

Kapitel
chapter



2.2

