

max. 350 bar



Dragmunstycken

Dragmunstyckena tillverkas i rostfritt och är speciellt avsedda för fastighetsspöling. Munstycket har bra dragkraft eftersom strålvinklarna är 0 och 20 grader.

With Front jet

Order-No.	Designation	Weight Kg	Dimension mm LxØ	Connection	Inserts	Scope of application from
0901	Z 253	0,08	32x25	1/8"	RS 4 Drills	Ab ½ DN 40
0903	Z 255	0,10	40x30	1/4"	VS 1x M4 x 1 VA RS 6 x M4 x 0,7 VA ceramic sapphire	Ab ½ DN 60
0904	Z 501	0,25	38x40	1/2"	VS 1xM6 x 1 VA RS 6 x M4 x 0,7 VA ceramic sapphire	Ab ½ DN 80
0905	Z 502	0,30	55x40	1/2"	VS 1xM6 x 1 VA RS 6 x M4 x 0,7 VA ceramic sapphire	Ab ½ DN 80

Pressure Nozzles made of stainless steel

Pressure nozzles made of stainless steel achieve outstanding pressure force and cleaning performance due to the deflection of the flow. They are suitable for small sewers with heavily soiled pipes and long reaches.

VS= Forward jet RS= Backward jet

The angles of the nozzles / holes are 0°/20°.

Ceramic inserts you will find on chapter IV. Adapters for reducing or increasing connection and Rotating Joints you will find at chapter VI.

