


max. 350 bar

Frontstrålmunstycken för vattenåtervinning.

R = framåtspolning rund, F = Framåtspolning flat



## Forward Jet Nozzle


with ceramic inserts also suitable for water-recycling

R = Forward jet round F = Forward jet flat Ceramic Inserts you will find on chapter IV.

Order-No.	Designation	Weight KG	Dimension mm L x B x H	Connection	Inserts
1301	V 01R K	0,13	50 x 30	1/2"	M 8 ceramic
1302	V 02R K	0,40	70 x 38	3/4"	M 10x1 ceramic
1303	V 03R K	0,76	84 x 50	1"	M 10x1 ceramic

Frontstrålmunstycken, rostfritt stål.

R = framåtspolning rund, F = Framåtspolning flat



## Forward Jet Nozzle made of Stainless Steel

R = forward jet round F = forward jet flat. We also have adapters for reducing or increasing connection please look at chapter VI.2 and VI.3. forward Jet Nozzles with ceramic are suitable for water-recycling.

Order-No.	Designation	Weight Kg	Dimension mm L x Ø	Connection	Inserts
1304	V 01R	0,13	50 x 30	1/2"	drilled
1305	V 01F	0,13	50 x 30	1/2"	1/4" Steel-Insert
1306	V 02R	0,40	70 x 38	3/4"	drilled
1307	V 02F	0,40	70 x 38	3/4"	1/4" Steel-Insert
1308	V 03R	0,76	84 x 50	1"	drilled
1309	V 03F	0,76	84 x 50	1"	1/4" Steel-Insert

Vretmaskin, Box 7138, 174 07 Sundbyberg Tel. 08-628 07 60, Fax 08-628 91 25  
Vretmaskin, Väpnaregatan 4, 281 50 Hässelholm, Tel. 0451-102 60

