

max. 350 bar

## Kombinationsmunstycken

Kombinationsmunstyckena tillverkas i rostfritt eller härdat stål. Detta munstycke är en kombination av Bomb- och Granat-munstyckena eftersom dysorna har olika strålvinkel.



With front jet



### / Stainless Steel

Order-No.	Designation	Weight Kg	Dimension mm L x Ø	Connection	Inserts	Scope of application from
0801	S 050 VA	1,0	80x50	1/2"	6 x M6x1 ceramic	Ab 1/2 DN 80
0802	S 05 VA Profi-EV Egg	0,5	55x50	1/2"	5 + 1 x M6x1 ceramic	Ab 1/2 DN 80

### / Hardened Steel

Order-No.	Designation	Weight	Dimension mm L x Ø	Connection	Inserts	Scope of application from
0803	S 075	1,4	100x55	3/4"	6 x M6x1 ceramic	Ab 1/2 DN 150
0804	S 100	2,5	105x75	1"	8 + 1 x M10x1 ceramic	Ab 1/2 DN 200
0805	S 101	3,6	135x80	1"	10+1 x M10x1 ceramic	Ab 1/2 DN 250
0806	S 125	5,5	150x90	1 1/4"	10+1 x M10x1 ceramic	Ab 1/2 DN 400

## Combination Nozzle

Combination Nozzle manufactured from stainless steel and hardened steel. Efficient Nozzles for all purposes. The Combination Nozzles have alternating jet angles and therefore provide optimal pressure and cleaning capability. These Nozzles combine the positive capabilities of the Bomb Nozzles and the Granat Nozzles.

The angles of the Nozzles will be 10°/20° and regarding the Nozzle S 050 25° and the S 051 30° respectively. Ceramic inserts you will find on chapter IV. Adapters for reducing or increasing connection and Rotating Joints you will find at chapter VI.

**Tipp:**  
Possible to use with flat jet

Vretmaskin, Box 7138, 174 07 Sundbyberg Tel. 08-628 07 60, Fax 08-628 91 25  
Vretmaskin, Våpnaregatan 4, 281 50 Hässelholm, Tel. 0451-102 60

