

max. 300 bar

Vibrerande rotermunstycken

Dessa roterdysor vibrerar för att slå loss avlagringar i röret. Kräver mycket vatten. OBS! får inte användas i keramikrör



Tipp:
To use with rotating joints!

Order-No.	Designation	Weight Kg	Dimension mm	Connection	Inserts	Scope of application from
2960	RTK VIP 28	0,15	L x Ø 60x28	1/4"	4xM4 Keramik/ceramic / Drills	Ab / 2 DN 30-60
2961	RTK VIP 40	0,55	L x Ø 83x40	1/2"	4xM6 Keramik/ceramic / Drills	Ab / 2 DN 70-100
2962	RTK VIP 50	1,0	L x Ø 93x50	3/4"	7xM6 Keramik/ceramic / Drills	Ab / 2 DN 70-150
2963	RTK VIP 60	1,4	L x Ø 103x60	1"	RS 3xM8 + Rot 4xM6 Keramik/ceramic / Drills	Ab / 2 DN 100-300
2964	RTK VIP 100	7,4	L x Ø 180x100	1"	7xM10x1 Keramik/ceramic / Drills	Ab / 2 DN 200-600

Rotor Vibration-Nozzle RTK-Rotor max. 300 bar

Special heavy rotationbody let those nozzle vibrate, to remove cement, mineral deposits in PVC, concrete- and steelpipes, water consumption 100 - 700 l/min. Working pressure: up to 300 bar.

Ceramic inserts you will find on chapter IV. Adapters for reducing or increasing connection and Rotating Joints you will find at chapter VI.

Achtung / Attention
Not to use in ceramic pipesystems!

